


-  Pumpe / Pump  
 Magnetventil / Solenoid valve  
 Mengenregler / Flow meter  
 Schmutzfänger / Strainer



Gültig für / valid for:

BM	Maschine / machine	y (l/min)	Maschine / machine	y (l/min)
90	MTF 4-xxxx MMLM	2,6	MTR 4-xxx MMMM	2,3
95	MTF 4-xxxx MMLM	2,7	MTR 4-xxx MMLM	2,5
100	MTF 4-xxxx MMLM	2,7	MTR 4-xxx MMLM	2,5
110	MTF 4-xxxx MMLM	2,7	MTR 4-xxx MMLM	2,7
115	MTF 4-xxxx MMLM	2,7	MTR 4-xxx MMLM	2,7
120	MTF 4-xxxx MMLM	2,7	MTR 4-xxx MMLM	2,7
125	MTF 4-xxxx MMLM	2,7	MTR 4-xxx MMLM	2,7
130	MTF 4-xxxx MMLM	2,8	MTR 4-xxx MMLM	3,0

y = Durchfluss / Flow rate

BM=90,95,100,110,115,120,125,130\_WQ=00,10,30\_ERG=10,15\_NU=00

winterhalter

OPTION  
 Osmose Wasser umschaltbar  
 Demineralized water switchable

Enthärtetes Wasser; max. 20°C  
 Softened water; max. 20°C  
 oder / or  
 Osmose Wasser  
 Demineralized water